

Libellus Datasheet

Sensirion Sensor Data Exchange Platform



Features

- Certificate & data distribution platform
- Individualized certificates
- Compatible with every ecosystem
- Available for products bought in distribution
- All certified Sensirion products
- Accessible for any volume
- Web access
- API access

General Description

Libellus¹ is a cloud storage platform providing certificates and other sensor-specific data to customers of Sensirion and other interested parties. Currently, ISO17025 certificates are available for STS32, STS33, and SHT33, while additional sensor-specific data and documentation will be added in future versions of Libellus. Web and API access is available to registered users only.

¹ Registered Trademark. Name derived from Latin: A libellus (plural libelli) was any brief document written on individual pages (as opposed to scrolls or tablets) in the Roman Empire, particularly official documents issued by governmental authorities.

Contents

Features	1
General Description.....	1
1 Overview	3
2 Content Specifications.....	3
3 Access.....	3
3.1 Registration.....	3
3.2 Web access	3
3.3 API access.....	Error! Bookmark not defined.
4 Certificate Individualization.....	4
5 Sensor Operation	4
5.1 I ² C Communication.....	Error! Bookmark not defined.
6 Revision History.....	5

Preliminary

1 Overview

Libellus is a secure cloud-service hosted by Sensirion for the exchange of sensor specific data between Sensirion, it's customers, and other interested parties, where access is only available as a registered user.

2 Hosted Content

Introduced for the exchange of sensor specific data, Libellus currently hosts:

1. ISO 17025 certification for STS32, STS33, and SHT33.
2. Future content tbd.

The ISO17025 certification data is available in the formats of:

1. PDFs,
2. CSVs,
3. 7z compressed folders, and
4. JSON links.

3 Access

3.1 Registration

Libellus is only accessible to registered users, which must demonstrate valid interest in Sensirion's products. Customer data necessary for identity and affiliation verification is stored only for internal use and never shared with or sold to third parties. Sensirion reserves the right to refuse registration with and without cause. User specific data is neither visible, nor accessible to any other users, yet Sensirion monitors login activities for prevention of misuse. Furthermore, users can be blocked by Sensirion for any improper actions.

User registration is available through libellus.sensirion.com, where users can obtain their personal API token (acting as username – password combination), valid for web and API access.

3.2 Access

For testing purposes and access to small numbers of documents and small data sets, access through the Libellus Web interface found at libellus.sensirion.com, is strongly recommended.

When larger number of requests need to be processed, API access is recommended, as described on libellus.sensirion.com/API.

In addition, the Sensirion sensor serial number is necessary to access data on Libellus. Kindly find instructions on how to extract the serial number in the corresponding sensor datasheets.

4 Certificate Individualization

End customers often have no possibilities to derive the serial number of the Sensirion sensor within a device, which would be needed to retrieve the corresponding certificate. Therefore, Sensirion offers the possibility to add a preface to the calibration certificate, creating the link between a customer device ID, and the built-in sensor ID. By optionally providing device manufacturer name and device ID during the certificate request on Libellus, the concatenated document, *i.e.*, preface and certificate, can be treated like any other available certificate.

Kindly find the instructions described on libellus.sensirion.com/about.

5 Service Level Agreement

Libellus is based on MS Azure CDN, making the [Azure CDN Service level agreement](#) part of this offering. Based and dependent on the MS Azure CDN, Sensirion furthermore guarantees 24/7 uptime and availability during 360 days per year. Planned downtime is announced to all users and on the Libellus landing page two weeks in advance.

During uptime, 99.5% of correct request will result in the correct answer, *e.g.* requesting a certificate using a correct combination of token, serial number, other necessary parameter, and following the right syntax, will yield the download of the requested certificate in 99.5% of all attempts.

This excludes:

1. Influence of factors outside our reasonable control (for example, natural disaster, war, acts of terrorism, riots, government action, or a network or device failure external to our data centers, including at your site or between your site and our data center);
2. Influence that results from the use of services, hardware, or software not provided by Sensirion, including, but not limited to, issues resulting from inadequate bandwidth or related to third-party software or services;
3. Requests made during preview, pre-release, beta or trial versions.
4. Results from faulty input, instructions, or arguments (for example, requests to access files that do not exist);
5. Maintenance windows as described above.

6 Revision History

Date	Version	Page(s)	Changes
November 2022	0.1	all	Initial release, preliminary version.

Preliminary

Important Notices

Warning, Personal Injury

Do not use this product as safety or emergency stop devices or in any other application where failure of the product could result in personal injury. Do not use this product for applications other than its intended and authorized use. Before installing, handling, using or servicing this product, please consult the data sheet and application notes. Failure to comply with these instructions could result in death or serious injury.

If the Buyer shall purchase or use SENSIRION products for any unintended or unauthorized application, Buyer shall defend, indemnify and hold harmless SENSIRION and its officers, employees, subsidiaries, affiliates and distributors against all claims, costs, damages and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if SENSIRION shall be allegedly negligent with respect to the design or the manufacture of the product.

ESD Precautions

The inherent design of this component causes it to be sensitive to electrostatic discharge (ESD). To prevent ESD-induced damage and/or degradation, take customary and statutory ESD precautions when handling this product. See application note "ESD, Latchup and EMC" for more information.

Warranty

SENSIRION warrants solely to the original purchaser of this product for a period of 12 months (one year) from the date of delivery that this product shall be of the quality, material and workmanship defined in SENSIRION's published specifications of the product. Within such period, if proven to be defective, SENSIRION shall repair and/or replace this product, in SENSIRION's discretion, free of charge to the Buyer, provided that:

- notice in writing describing the defects shall be given to SENSIRION within fourteen (14) days after their appearance;
- such defects shall be found, to SENSIRION's reasonable satisfaction, to have arisen from SENSIRION's faulty design, material, or workmanship;
- the defective product shall be returned to SENSIRION's factory at the Buyer's expense; and
- the warranty period for any repaired or replaced product shall be limited to the unexpired portion of the original period.

This warranty does not apply to any equipment which has not been installed and used within the specifications recommended by SENSIRION for the intended and proper use of the equipment. EXCEPT FOR THE WARRANTIES EXPRESSLY SET FORTH HEREIN, SENSIRION MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCT. ANY AND ALL WARRANTIES, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED AND DECLINED.

SENSIRION is only liable for defects of this product arising under the conditions of operation provided for in the data sheet and proper use of the goods. SENSIRION explicitly disclaims all warranties, express or implied, for any period during which the goods are operated or stored not in accordance with the technical specifications.

SENSIRION does not assume any liability arising out of any application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. All operating parameters, including without limitation recommended parameters, must be validated for each customer's applications by customer's technical experts. Recommended parameters can and do vary in different applications.

SENSIRION reserves the right, without further notice, (i) to change the product specifications and/or the information in this document and (ii) to improve reliability, functions and design of this product.

Headquarters and Subsidiaries

Sensirion AG
Laubisruetistr. 50
CH-8712 Staefa ZH
Switzerland

phone: +41 44 306 40 00
fax: +41 44 306 40 30
info@sensirion.com
www.sensirion.com

Sensirion Taiwan Co. Ltd
phone: +886 3 5506701
info@sensirion.com
www.sensirion.com

Sensirion Inc., USA
phone: +1 312 690 5858
info-us@sensirion.com
www.sensirion.com

Sensirion Japan Co. Ltd.
phone: +81 3 3444 4940
info-jp@sensirion.com
www.sensirion.com/jp

Sensirion Korea Co. Ltd.
phone: +82 31 337 7700~3
info-kr@sensirion.com
www.sensirion.com/kr

Sensirion China Co. Ltd.
phone: +86 755 8252 1501
info-cn@sensirion.com
www.sensirion.com/cn

To find your local representative, please visit
www.sensirion.com/distributors